

In the claims

Please amend the claims as follows:

1. Withdrawn.
2. Withdrawn.
3. Withdrawn.
4. Withdrawn.
5. Withdrawn.
6. Withdrawn.
7. Withdrawn.
8. Withdrawn.
9. Withdrawn.
10. Withdrawn.
11. Withdrawn.
12. (Currently amended) In combination, a heat shield and a vibration insulator for a vehicle exhaust system; the combination comprising:
a vibration insulator having a frame with an outer surface, a front surface and a rear surface; and
a flexible, non-metallic heat shield formed of a heat resistant material and having a cup-shaped body defining a chamber ; ~~the chamber having~~ with an inner surface; ~~the heat shield and vibration insulator being complementarily shaped and when the~~

~~vibration insulator is~~ said vibration insulator being held within the chamber, wherein at least a portion of the outer surface and front surface of the vibration insulator ~~he~~ lies in contact with the inner surface of the chamber; the heat shield ~~adapted to~~ thermally ~~insulate~~ insulating the vibration insulator from heat generated by the vehicle exhaust system ~~an external heat source~~.

13. (Canceled)

14. (Currently amended) The combination of claim ~~43~~12, wherein the heat shield is manufactured from an elastomer.

15. (Original) The combination of claim 14, wherein the heat shield is manufactured from a silicone elastomer.

16. (Original) The combination of claim 15, wherein the heat shield is manufactured from a silicone elastomer selected from the group ASTM D2000 classification GE, FC, FE and FK.

17. (Original) The combination of claim 14, wherein the elastomer is fluorolastomer.

18. (Original) The combination of claim 14, wherein the body is manufactured

from ethylene acrylic.

19. (Previously submitted) In combination, a heat shield and a vibration insulator for a vehicle exhaust system; the combination comprising:
a vibration insulator having a frame with an outer surface; a front surface and a rear surface; and
a heat shield having a cup-shaped body defining a chamber; the vibration insulator being substantially disposed within the chamber with the heat shield adapted to protect the vibration insulator against an external heat source; wherein the heat shield includes at least one internal bead projecting into the chamber; the bead at least partially retaining the heat shield on the vibration insulator.
20. (Previously submitted) The combination of claim 19, wherein the vibration insulator includes an external projection; the projection cooperating with the bead to hold the heat shield on the vibration insulator.
21. (Currently amended) The combination of claim ~~19~~ 20, wherein the heat shield and insulator form air spaces between them.
22. (Previously submitted) The combination of claim 21, wherein the frame of the insulator includes protuberances and valleys defines between the protuberances; wherein the body of the heat shield includes sidewalls and a

bottom wall; and the air spaces are formed between the valleys of the frame and the sidewalls of the heat shield.

23. (Previously submitted) In combination, a heat shield and a vibration insulator for a vehicle exhaust system; the combination comprising:

a vibration insulator having a frame with an outer surface, a front surface and a rear surface; the frame of the vibration insulator including protuberances which have a second front surface that extends further outwardly from the frame than the front surface of the frame; and

a heat shield having a cup-shaped body defining a chamber; the vibration insulator being substantially disposed within the chamber so that the heat shield is adapted to protect the vibration insulator against an external heat source; and wherein the second front surface of the protuberances abuts the heat shield and air spaces are formed between the heat shield and the front surface of the frame of the vibration insulator.

24. (Currently amended) The combination of claim ~~12~~23; wherein the body of the heat shield is shaped like a diamond with rounded corners.

25. (Original) The combination of claim 24, wherein the body includes straight sidewalls extending between the rounded corners.

26. (Currently amended) An improved motor vehicle having a chassis and an exhaust system, the exhaust system having an exhaust pipe and a hanger connecting the exhaust pipe to the chassis; a vibration insulator disposed on the hanger, the vibration insulator having a frame with an outer surface and a front surface; the improvement comprising:

a flexible, non-metallic heat shield formed of a heat resistant material; the heat shield having a cup-shaped body defining a chamber that has an inner lining; the chamber sized to receive the vibration insulator so that when the vibration insulator is held within the chamber, the inner lining of the chamber contacts at least a portion of the outer surface and the front surface of the vibration insulator; ~~the body adapted to~~ and wherein the heat shield thermally insulates the vibration insulator from heat generated by the exhaust system ~~shield the chamber from an external heat source.~~

27. (Previously submitted) The improved motor vehicle of claim 26, wherein the heat shield is manufactured from a flexible, heat resistant material.

28. (Previously submitted) The improved motor vehicle of claim 27, wherein the heat shield is manufactured from an elastomer.

29. (Previously submitted) The improved motor vehicle of claim 28, wherein the heat shield is manufactured from a silicone elastomer.

30. (Previously submitted) The improved motor vehicle of claim 29, wherein the heat shield is manufactured from a silicone elastomer selected from the group ASTM D2000 classification GE, FC, FE and FK.
31. (Previously submitted) The improved motor vehicle of claim 28, wherein the elastomer is fluorolastomer.
32. (Currently amended) The ~~improvement~~ improved motor vehicle of claim 27, wherein the body is manufactured from ethylene acrylic.
33. (Currently amended) The ~~improvement~~ improved motor vehicle of claim 26, wherein the heat shield provides air gaps between the heat shield and the insulator.
34. (Withdrawn).
35. (Previously submitted) The combination of claim 12, in which the heat shield is frictionally secured to the vibration insulator.
36. (Currently amended) In combination, a heat shield and a vibration insulator for a vehicle exhaust system; the combination comprising:
a vibration insulator having a frame with an outer surface; a front surface

and a rear surface; the vibration insulator defining at least one aperture extending from the front surface through to the rear surface;

a flexible, non-metallic heat shield formed from a heat resistant material;
the heat shield having a cup-shaped body defining a chamber; the chamber having a sidewalls and a bottom wall, the bottom wall defining at least one hole therein; and when the vibration insulator is received within the chamber of the heat shield; the aperture in the vibration insulator substantially aligns with the hole in the heat shield.

37. (Currently amended) The combination of claim 36, wherein the vibration insulator defines two apertures extending from the front surface through the rear surface thereof; and wherein the bottom wall of the heat shield defines two holes therein, and the positions of the two apertures in the vibration insulator substantially align with the two holes in the heat shield; and the vibration insulator and heat shield are adapted to be connected to a vehicle body and ~~an~~ the exhaust system via two connectors and the connectors are receivable through the aligned apertures and holes.

38. (Canceled)

39. (Previously submitted) The combination of claim 38, wherein the heat shield is manufactured from a silicone elastomer.

40. (Previously submitted) The combination of claim 19, wherein the vibration insulator defines at least one aperture extending from the front surface through to the rear surface; and wherein the heat shield chamber has sidewalls and a bottom wall and the bottom wall defines at least one hole therein; and when the vibration insulator is received within the chamber of the heat shield, the aperture in the vibration insulator substantially aligns with the hole in the heat shield.
41. (Previously submitted) The combination of claim 23, wherein the vibration insulator defines at least one aperture extending from the front surface through to the rear surface; and wherein the heat shield chamber has sidewalls and a bottom wall and the bottom wall defines at least one hole therein; and when the vibration insulator is received within the chamber of the heat shield, the aperture in the vibration insulator substantially aligns with the hole in the heat shield.
42. (New) The combination of claim 19, in which the heat shield is frictionally secured to the vibration insulator.
43. (New) In combination, a heat shield and a vibration insulator for a vehicle exhaust system; the combination comprising:
a vibration insulator which flexes, stretches and contracts in response to movements in the vehicle exhaust system; and
a non-metallic heat shield formed of a heat resistant, flexible material and having

a cup-shaped body defining a chamber for receiving said vibration insulator therein;
and wherein the heat shield thermally insulates the vibration insulator from heat
generated by the vehicle exhaust system; whereby the heat shield flexes, stretches and
contracts along with the vibration insulator.

44. (New) The combination of claim 43, wherein the heat shield is manufactured
from an elastomer.

45. (New) The combination of claim 44, wherein the heat shield is manufactured
from a silicone elastomer.

46. (New) The combination of claim 45, wherein the heat shield is manufactured
from a silicone elastomer selected from the group ASTM D2000 classification
GE, FC, FE and FK.

47. (New) The combination of claim 44, wherein the elastomer is fluorolastomer.

48. (New) The combination of claim 44, wherein the body is manufactured from
ethylene acrylic.